

Specifications

Parameter	Minimum	* Typical	Maximum	
Frequency Range (MHz)	1710		1785	
Insertion Loss (dB)		< .20	.30	
Isolation (dB)	22	> 25		
Return Loss (dB)	22	> 25		
FWD IMD: 2T at 37W per T		7.5		
5MHz Spacing (dBc)		75		

 \star Typical Values Represent Mid-Band Performance @ +23 °C. Tab dimensions: 1.00[.039]W x 2.5[.10]L x .20[.008]T

Power & Temperature Ratings

Parameter	Maximum	
Forward PWR Peak/AVG	1000/100 Watts	
Reverse Power CW	100 Watts	
Operating Temperature	-40 to +85° C	
Storage Temperature	-40 to +95° C	

CW CIRCULATOR MODEL: RFCR2412

THIRD ANGLE PROJECTION		DECL (A)				
APPROVALS	DATE	1				
DRAWN BY: HV	04/12/13					
CHECKED BY: P.T	04/13/13	TITLE				
DESIGN BY: P.T						
ENGINEER BY: P.T	01/15/13					
MFG. ENGR. L.T	02/12/13	SIZE ONGENO.		IREV.		
Q.A.					110.00	1
PROG. MGMT/MKT				UR24	+12-05	'
		SCALE: FULL			SHEET 1 OF 1	
	DRAWN BY: HV CHECKED BY: P.T DESIGN BY: P.T ENGINEER BY: P.T MFG. ENGR. L.T Q.A.	DRAWN BY: HV 04/12/13 CHECKED BY: P.T 04/13/13 DESIGN BY: P.T 01/15/13 ENGINEER BY: P.T 01/15/13 MFG. ENGR. L.T 02/12/13 Q.A.	DRAWN BY: HV 04/12/13 CHECKED BY: P.T 04/13/13 DESIGN BY: P.T 01/15/13 ENGINEER BY: P.T 01/15/13 MFG. ENGR. L.T 02/12/13 Q.A. PROG. MGMT/MKT SIZE A	DRAWN BY: HV 04/12/13 CHECKED BY: P.T 04/13/13 DESIGN BY: P.T 01/15/13 ENGINEER BY: P.T 01/15/13 MFG. ENGR. L.T 02/12/13 Q.A. PROG. MGMT/MKT HV 04/12/13 TITLE OI/15/13 SIZE CAGE NO. A	DRAWN BY: HV 04/12/13 CHECKED BY: P.T 04/13/13 DESIGN BY: P.T 01/15/13 ENGINEER BY: P.T 01/15/13 MFG. ENGR. L.T 02/12/13 Q.A. PROG. MGMT/MKT HV 04/12/13 TITLE OUTLINE/S OUTLINE/S A CAGE NO. DWG NO. CR24	DRAWN BY: HV 04/12/13 CHECKED BY: P.T 04/13/13 DESIGN BY: P.T 01/15/13 ENGINEER BY: P.T 01/15/13 MFG. ENGR. L.T 02/12/13 Q.A. PROG. MGMT/MKT HV 04/12/13 TITLE OUTLINE/SPECS OUTLINE/SPECS CR2412-OS