

Specifications

Parameter	Minimum	* Typical	Maximum	
Frequency Range (MHz)	2010		2090	
Insertion Loss (dB)		< .20	.30	
Isolation (dB)	22	> 25		
Return Loss (dB)	22	> 25		
FWD IMD: 2T at 37W per T		75		
5MHz Spacing (dBc)		75		

* Typical Values Represent Mid-Band Performance @ +23 °C.
Tab dimensions: 1.00[.039]W x 2.5[.10]L x .20[.008]T

Power & Temperature Ratings

Parameter	Maximum		
Forward PWR Peak/AVG	1000/100 Watts		
Reverse Power CW	100 Watts		
Operating Temperature	-40 to +85° C		
Storage Temperature	-40 to +95° C		

CW CIRCULATOR MODEL: RFCR2722

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS [INCHES]: TOLERAŅCES ARE:	THIRD ANGLE PROJECTION		DECL (A)					
1 PLACE DECIMAL ±.2 [±.01] ANGULAR: ±1.0° 2 PLACE DECIMAL ±.10 [±.004] SURFACE ROUGHNESS 16/	APPROVALS	DATE						
REMOVE ALL BURRS AND BREAK SHARP EDGES. SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1	DRAWN BY: HV	04/12/13						
DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI 846.1	CHECKED BY: P.T	04/13/13	TITLE					
PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RE	DESIGN BY: P.T	01/15/13	OUTLINE/SPECS					
CIRCULATOR ISOLATOR Inc. (RFCI) AND IS PROVIDED SOLELY FOR INFORMATION PURPOSES.	ENGINEER BY: P.T	01/15/13	OUTLINE/OF LOO					
THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED, NOR SHALL IT BE DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL."	MFG. ENGR. L.T	02/12/13	SIZE	ZE CAGE NO. DWG NO.				REV.
	Q.A.					`	4	
	PROG. MGMT/MKT		Α		CR2722-0		>	'
DO NOT SCALE DRAWING			SCALE	E: FULL		S	HEET 1 OF 1	