

Specifications

Parameter	Minimum	Typical	Maximum
Frequency Range (MHz)	860		960
Insertion Loss (dB)		< .25	.30
Isolation (dB)	22	> 23	
Return Loss (dB)	22	> 23	
FWD IMD: 2T at 37W per T		75	
5MHz Spacing (dBc)		75	

Power & Temperature Ratings

Parameter	ameter Maximum		
Forward PWR Peak/AVG	1000/200 Watts		
Reverse Power CW	200 Watts		
Operating Temperature	-40 to +85° C		
Storage Temperature	-40 to +95° C		

Notes

- 1. Typical Values Represent Mid-Band Performance @ +23 °C.
- 2. Tab dims: .64[.025]Width x 3.0[.12]Length x .20[.008]Thick

CW CIRCULATOR MODEL: RFCR2225

UNLESS OTHERWISE SPECIFIED all dimensions are in millimeters (inches): tolerances are:	THIRD ANGLE PROJECTION							
1 PLACE DECIMAL ±.2 [±.01] ANGULAR: ±1.0° SURFACE ROUGHNESS 16/	APPROVALS	DATE						
REMOVE ALL BURRS AND BREAK SHARP EDGES. SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1	DRAWN BY: HV	04/13/13						
DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI Y14.5	CHECKED BY: P.T	04/14/13	TITLE					
PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RE	DESIGN BY: P.T	01/10/13		OUTLINE/SPECS				
CIRCULATOR ISOLATOR Inc. (RFCI) AND IS PROVIDED SOLELY FOR INFORMATION PURPOSES.	ENGINEER BY: P.T	01/10/13						
THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED. NOR SHALL IT BE	MFG. ENGR. L.T	02/10/13	SIZE	CAGE NO.	DWG NO.		REV.	
DESIGN OR CONSTRUCT AIM TO THE TEEM DEPTILED, NOR SHALL IT BE DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL."	Q.A.		_ ^	000000000000000000000000000000000000000		OF OC	1	
	PROG. MGMT/MKT		А		UR22	25-05		
DO NOT SCALE DRAWING			SCALE: FULL			SHEET 1 OF 1		