


DWG. NO.

REV



RoHS 2002/95/EC	The second second



Specifications

Parameter	Minimum	Typical	Maximum	
Frequency Range (N	5000		6500	
Insertion Loss (dB)	P1-P2 P2-P3		< .70 < .45	0.90 0.50
Isolation (dB)	P2-P1 P3-P2	36 17	> 42 > 20	
Return Loss (dB)		17	> 20	

Power & Temperature Ratings

Parameter	Maximum
Forward PWR Peak/AVG	500/35 Watts
Reverse Power CW	10 Watts
Operating Temperature	-40 to +85° C
Storage Temperature	-40 to +95° C

NOTES:

- 1. Typical Values Represent Mid-Band Performance @ +23 °C.
- 2. Tab Dims: .62[.024]Width x 2.0[.08]Length x .20[.008]Thick.

CW DUAL CIRCULATOR MODEL: CR2878F3

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS [INCHES]: TOLERANCES ARE:		THIRD ANGLE PROJECTION								
1 PLACE DECIMAL ±.2 [±.01] 2 PLACE DECIMAL ±.10 [±.004]	ANGULAR: ±1.0° SURFACE ROUGHNESS 16	APPROV	/ALS	DATE	I RECI					
REMOVE ALL BURRS AND BREAK SHARP EDGES. SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1 DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI Y14.5		DRAWN BY:	HV	04/19/13						
		CHECKED BY:	P.T	04/20/13						
PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RF CIRCULATOR ISOLATOR INE. (RFCI) AND IS PROVIDED SOLELY FOR INFORMATION PURPOSES. THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED, NOR SHALL IT BE DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL."		DESIGN BY:	P.T	04/01/13						
		ENGINEER BY:	P.T	04/01/13						
		MFG. ENGR.	L.T	4/21/13	SIZE	SIZE CAGE NO. DWG NO.			REV.	
		Q.A.			A OAGENO.			D0070E0 OC		
		PROG. MGMT/MKT					CR2878F3-O		5-05	
DO NOT SCALE	DRAWING			SCALE: FULL				SHEET 1 OF 1		