


THIS DRAWING HAS BEEN GENERATED BY A CAD SYSTEM. CHANGES SHALL ONLY BE INCORPORATED AS DIRECTED BY THE DESIGN ACTIVITY. DO NOT REVISE MANUALLY.

| REVISIONS |                 |      |          |          |
|-----------|-----------------|------|----------|----------|
| REV.      | DESCRIPTION     | ECO  | DATE     | APPROVED |
| 1         | INITIAL RELEASE | I.R. | 04/22/13 | P.T      |



**Specifications**

| Parameter             | Minimum | Typical | Maximum |
|-----------------------|---------|---------|---------|
| Frequency Range (MHz) | 8300    |         | 8800    |
| Insertion Loss (dB)   |         |         |         |
| P1-P2; P3-P4          |         | < .50   | 0.60    |
| P2-P3; P4-P1          |         | < .30   | 0.35    |
| Isolation (dB)        |         |         |         |
| P2-P1; P4-P3          | 40      | > 48    |         |
| P3-P2; P1-P4          | 20      | > 23    |         |
| Return Loss (dB)      | 20      | > 23    |         |

**Power & Temperature Ratings**

| Parameter             | Maximum       |
|-----------------------|---------------|
| Forward PWR Peak/AVG  | 500/35 Watts  |
| Reverse Power CW      | 35 Watts      |
| Operating Temperature | -40 to +85° C |
| Storage Temperature   | -40 to +95° C |

- NOTES:  
 1. Typical Values Represent Mid-Band Performance @ +23 °C.  
 2. Tab Dims: .62[.024]Width x 2.0[.08]Length x .20[.008]Thick.

**CW DUAL CIRCULATOR MODEL: CR2884F**

|  |  |  |              |
|--|--|--|--------------|
| UNLESS OTHERWISE SPECIFIED<br>ALL DIMENSIONS ARE IN MILLIMETERS (INCHES):<br><br>TOLERANCES ARE:<br>1 PLACE DECIMAL ±.2 [±.01]    ANGULAR: ±1.0°<br>2 PLACE DECIMAL ±.10 [±.004]    SURFACE ROUGHNESS 16/  | THIRD ANGLE PROJECTION<br>   |  |              |
|  | REMOVE ALL BURRS AND BREAK SHARP EDGES.<br>SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1<br>DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI Y14.5 | APPROVALS<br>DRAWN BY: HV    04/19/13<br>CHECKED BY: P.T    04/20/13 |              |
| PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RF CIRCULATOR ISOLATOR Inc. (RFCI) AND IS PROVIDED SOLELY FOR INFORMATION PURPOSES. THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED, NOR SHALL IT BE DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL." | Q.A.<br>PROG. MGMT/MKT   | SIZE A    CAGE NO.    DWG NO. CR2884F-OS    REV. 1                   |              |
| DO NOT SCALE DRAWING   | SCALE: FULL  |  | SHEET 1 OF 1 |