







## **Specifications**

Parameter	Minimum	Typical	Maximum
Frequency Range (MHz)	430		460
Insertion Loss (dB)		< .40	.60
Isolation (dB)	46	> 52	
Return Loss (dB)	22	> 25	

## Notes:

- 1. Typical Values Represent Mid-Band Performance @ +23 °C.
- 2. Isolator Flange held to +85°C; 30 Min. maximum Duration.

## Power & Temperature Ratings

Parameter	Maximum			
Forward PWR Peak/AVG	1000/200 Watts			
Reverse Power CW	20 Watts			
Termination Rating (See Note 2)	20 Watts			
Operating Temperature	-20 to +85° C			
Storage Temperature	-40 to +95° C			

## CW 20W SMAf DUAL JUNCTION ISOLATOR MODEL SL3122F

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS (INCHES): TOLERANCES ARE:	THIRD ANGLE PROJECTION		RECI (A)					
1 PLACE DECIMAL ±.2 [±.01] ANGULAR: ±1.0° SURFACE ROUGHNESS 16/	APPROVALS	DATE						
REMOVE ALL BURRS AND BREAK SHARP EDGES. SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1	DRAWN BY:							
DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI 546.1	CHECKED BY:		TITLE					
PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RE	DESIGN BY:		OUTLINE/SPECS					
CIRCULATOR ISOLATOR Inc. (RFCI) AND IS PROVIDED SOLELY FOR INFORMATION PURPOSES.	ENGINEER BY:		OUTLINE/SI LOS					
THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED, NOR SHALL IT BE DISCLOSED, DUPICATED, OR COPIED FOR ANY PURPOSE, NOR MADE AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL."	MFG. ENGR.		SIZE	SIZE CAGE NO. DWG NO.				REV.
	Q.A.		A   5.1.5.2.1.5.1			IOOF (		1
	PROG. MGMT/MKT		A	<b>`</b>	SL31	22F-OS		
DO NOT SCALE DRAWING			SCALE:	FULL			SHEET 1 OF 1	