

## Specifications

Parameter	Minimum	Typical	Maximum	
Frequency Range (MHz)	2470		2730	
Insertion Loss (dB)		< .20	.30	
Isolation (dB)	22	> 25		
Return Loss (dB)	22	> 25		
FWD IMD: 2T at 37W per T		7.5		
5MHz Spacing (dBc)		75		

## Power & Temperature Ratings

DWG. NO.

SL2872-OS

REV

APPROVED

P.T

Maximum		
1000/200 Watts		
100 Watts		
100 Watts		
-40 to +85° C		
-40 to +95° C		

## Notes

- 1. Typical Values Represent Mid-Band Performance @ +23 °C.
- 2. Isolator Flange held to +85°C; 30 Min. maximum Duration.
- 3. Tab dims: .64[.025]Width x 3.0[.12]Length x .20[.008]Thick

CW 100W GW ISOLATOR MODEL: RFSL2872

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS [INCHES]: TOLERANCES ARE:	THIRD ANGLE PROJECTION	<del>]</del>		DECL (A)				
1 PLACE DECIMAL ±.2 [±.01] ANGULAR: ±1.0° 2 PLACE DECIMAL ±.10 [±.004] SURFACE ROUGHNESS 16/	APPROVALS	DATE	1					
REMOVE ALL BURRS AND BREAK SHARP EDGES. SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI 846.1	DRAWN BY: HV	04/16/13						
DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI 846.1	CHECKED BY: P.T	04/17/13	TITLE					
PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RE	DESIGN BY: P.T	12/12/12	OUTLINE/SPECS					
CIRCULATOR ISOLATOR Inc. (RFCI) AND IS PROVIDED SOLELY FOR INFORMATION PURPOSES.	ENGINEER BY: P.T	01/10/13			,			
THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED. NOR SHALL IT BE	MFG. ENGR.	04/19/13	SIZE	SIZE CAGE NO. DWG NO.			REV.	
DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE	Q.A.					070 00	1	
AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL."	PROG. MGMT/MKT		Α		SL2	872-OS	•	
DO NOT SCALE DRAWING				E: FULL		SHEE	SHEET 1 OF 1	
			_		•	•		