


THIS DRAWING HAS BEEN GENERATED BY A CAD SYSTEM. CHANGES SHALL ONLY BE INCORPORATED AS DIRECTED BY THE DESIGN ACTIVITY. DO NOT REVISE MANUALLY.



| REVISIONS | | | | |
|-----------|-----------------|------|----------|----------|
| REV. | DESCRIPTION | ECO | DATE | APPROVED |
| 1 | INITIAL RELEASE | I.R. | 09/06/13 | P.T |



Specifications

| Parameter | Minimum | Typical | Maximum |
|-----------------------|---------|---------|---------|
| Frequency Range (MHz) | 700 | | 850 |
| Insertion Loss (dB) | | < .40 | .50 |
| Isolation (dB) | 20 | > 23 | |
| Return Loss (dB) | 20 | > 23 | |

Notes:

1. Typical Values Represent Mid-Band Performance @ +23 °C.
2. Isolator held to +85°C; 30 Min. maximum Duration.

Power & Temperature Ratings

| Parameter | Maximum |
|---------------------------------|----------------|
| Forward PWR Peak/AVG | 2.0K/200 Watts |
| Reverse Power CW | 200 Watts |
| Termination Rating (See note 2) | 200 Watts |
| Operating Temperature | -40 to +85° C |
| Storage Temperature | -40 to +95° C |

SMaf 200W ISOLATOR MODEL: RFSL6173-T200

| | | | | | | | | |
|---|---|----------------------|------------------------------|-----------------------------------|-------------------------------|--|--|--|
| <p>UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS [INCHES]:</p> <p>TOLERANCES ARE:</p> <table border="1"> <tr> <td>1 PLACE DECIMAL ±.2 [±.01]</td> <td>ANGULAR: ±1.0°</td> </tr> <tr> <td>2 PLACE DECIMAL ±.10 [±.004]</td> <td>SURFACE ROUGHNESS 16/</td> </tr> </table> <p>REMOVE ALL BURRS AND BREAK SHARP EDGES. SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1 DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI Y14.5</p> <p>PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RF CIRCULATOR ISOLATOR Inc. (RFCI) AND IS PROVIDED SOLELY FOR INFORMATION PURPOSES. THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED, NOR SHALL IT BE DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL."</p> | 1 PLACE DECIMAL ±.2 [±.01] | ANGULAR: ±1.0° | 2 PLACE DECIMAL ±.10 [±.004] | SURFACE ROUGHNESS 16/ | <p>THIRD ANGLE PROJECTION</p> | | | |
| | 1 PLACE DECIMAL ±.2 [±.01] | ANGULAR: ±1.0° | | | | | | |
| 2 PLACE DECIMAL ±.10 [±.004] | SURFACE ROUGHNESS 16/ | | | | | | | |
| <p>APPROVALS</p> <p>DATE</p> | <p>DESIGN BY:</p> <p>ENGINEER BY:</p> <p>MFG. ENGR.</p> <p>Q.A.</p> <p>PROG. MGMT/MKT</p> | <p>OUTLINE/SPECS</p> | | | | | | |
| <p>DO NOT SCALE DRAWING</p> | <p>SCALE: FULL</p> | <p>SIZE A</p> | <p>CAGE NO.</p> | <p>DWG NO. SL6173-T200-OS</p> | <p>REV. 1</p> | | | |
| | | | | <p>SHEET 1 OF 1</p> | | | | |