





Finish:

Body Housing: Steel, Nickel plated Tab Lead: Be-Cu, Silver plated

Terminal:

Port (1)-(2): Input-Output Port (2)-(3): Input-Output Port (3)-(1): Input-Output

Specifications

Parameter	Minimum	Typical	Maximum
Frequency Range (MHz)	2200		2300
Insertion Loss: In-Out (dB)		< 0.20	0.30
Isolation: Out-In (dB)	22	> 25	
Return Loss: All Ports (dB)	22	> 25	
FWD IMD: 2T atW per T 5MHz Spacing (dBc)		tbd	

Permanent damage to the Device or reduce reliability if exceeding any of the limits

Port (1),(2)and (3): DC connected and floating as the only ground connection.

Power & Temperature Ratings

Parameter	Maximum	
Forward PWR Peak/CW	1000/100 Watts	
Reverse PWR Peak/CW	1000/100 Watts	
Operating Temperature	-40 to +85° C	
Storage Temperature	-40 to +95° C	

Notes:

- 1. Typical Values Represent Performance @ +23 °C
- 2. Tab Dimensions: 1.00 [.040]W x 2.5 [.10]L x 0.20 [.008]T
- S-Parameters to be measured by connecting Port 1 and 2 to VNA, and Port 3 to Load with return loss 30dB or higher
- 4. MATRIX BARCODE: PART No., SN, DATE CODE

CW CIRCULATOR MODEL: RFCR2847

